

THE 2020 ENTEGRA COACH QUICK-REFERENCE TOW GUIDE



LUXURY DIESEL MODELS

GAS CLASS A MODELS

CLASS C MODELS



	CORNERSTONE	ANTHEM	ASPIRE	REATA XL	REATA	EMBLEM	VISION	QWEST	ESTEEM	ODYSSEY
HITCH	20,000 lbs., 7/4-pin plug	15,000 lbs., 7/4-pin plug (10,000 lbs. on Aspire 38M and 40P)		10,000 lbs., 7/4-pin plug		5,000-pound receiver with dual connector, 7-pin plug		5,000-pound receiver with dual connector, 7-pin plug	7,500-lb. with 750-lb. tongue capacity, 7-pin plug	
CHASSIS	Spartan® K3 raised rail	Spartan K2 raised rail			Spartan K1 raised rail	Ford® F53 chassis		Mercedes 3500	Ford E-450 chassis	
EXTERIOR LENGTHS	44' 11"	43' 5" and 44' 11"	40' 11" – 44' 11"	37' 10" – 40' 11"	37' 10" – 39' 11"	38' 2" – 38' 8"	28'5" – 32' 2"	25' 2"	26' 8" – 32' 6"	
GCWR (LBS.) <small>GROSS COMBINED WEIGHT RATING</small>	74,000	67,000	51,000 – 64,000	42,000 – 46,320		30,000	23,000	15,250	22,000	
GVWR (LBS.) <small>GROSS VEHICLE WEIGHT RATING</small>	54,000	52,000	41,000 – 49,000	32,600 – 36,320		24,000	16,000 – 18,000	11,030	14,500	
PRO TIP: TO CALCULATE TOW RATING, SIMPLY SUBTRACT THE GVWR FROM THE GCWR.										
ENGINE	Cummins ISX 15L turbocharged, 605 HP	Cummins ISL 9L turbocharged, 450 HP		Cummins ISL 9L turbocharged, 380 HP	Cummins B 6.7 turbocharged, 360 HP	Triton® 6.8L V10, 320 HP		3.0L V6 BlueTEC Diesel, 188 HP	Triton 6.8L EFI V10, 305 HP	
TORQUE	1,950 lb.-ft. at 1,200 RPM	1,250 lb.-ft. at 1,400 RPM		1,150 lb.-ft. at 1,400 RPM	800 lb.-ft. at 1,800 RPM	460 lb.-ft.		325 lb.-ft.	420 lb.-ft.	
BRAKING	Safehaul tow air system					Front and rear disc, 4-wheel anti-lock		Front and rear disc, 4-wheel anti-lock	Power anti-lock	