

THE 2021 ENTEGRA COACH
QUICK-REFERENCE

TOW GUIDE



LUXURY DIESEL MODELS



	CORNERSTONE	ANTHEM	ASPIRE	REATTA XL	REATTA
HITCH	20,000 lbs., 7/4-pin plug	15,000 lbs., 7/4-pin plug (10,000 lbs. on Aspire 38M and 40P)		10,000 lbs., 7/4-pin plug	
CHASSIS	Spartan® K3 raised rail	Spartan K2 raised rail			Spartan K1 raised rail
EXTERIOR LENGTHS	44' 11"	43' 5" and 44' 11"	40' 11" – 44' 11"	37' 10" – 40' 11"	37' 10" – 39' 11"
GCWR (LBS.) <small>GROSS COMBINED WEIGHT RATING</small>	74,000	67,000	51,000 – 64,000	42,000 – 46,320	
GVWR (LBS.) <small>GROSS VEHICLE WEIGHT RATING</small>	54,000	52,000	41,000 – 49,000	32,600 – 36,320	
PRO TIP: TO CALCULATE TOW RATING, SIMPLY SUBTRACT THE GVWR FROM THE GCWR.					
ENGINE	Cummins® ISX 15L turbocharged, 605 HP	Cummins ISL 9L turbocharged, 450 HP		Cummins ISL 9L turbocharged, 380 HP	Cummins B 6.7 turbocharged, 360 HP
TORQUE	1,950 lb.-ft. at 1,150 RPM	1,250 lb.-ft. at 1,400 RPM		1,150 lb.-ft. at 1,400 RPM	800 lb.-ft. at 1,800 RPM
BRAKING	Spartan Safehaul tow vehicle air brake system				